

[Sign in](#)[Google](#)[Web](#) [Images](#) [Video](#) [News](#) [Maps](#) [more »](#)[Advanced Search](#)  
[Preferences](#)**Web**Results 1 - 10 of about 995,000 for **(j2ee server) (state server) (state objects)**. (0.20 seconds)**j2eeserver: J2EE Server Lifecycle**

J2eeServer – the management object for a J2EE server. StateManageable – a set of operations ... IDE User Interaction and J2EE Server State Transition: ...

[j2eeserver.netbeans.org/J2eeServerLifecycle.html](http://j2eeserver.netbeans.org/J2eeServerLifecycle.html) - 24k - [Cached](#) - [Similar pages](#)

**[PDF] JNDI State Replication in OC4J 10g (10.1.2 and 10.1.3)**

File Format: PDF/Adobe Acrobat - [View as HTML](#)

As an essential part of the J2EE specification, JNDI provides uniform naming and ... JNDI state replication in Oracle Application Server and OC4J 10g ...

[www.oracle.com/technology/tech/java/oc4j/10131/whitepapers/OC4J-TWP-JNDI-STATE-10131.pdf](http://www.oracle.com/technology/tech/java/oc4j/10131/whitepapers/OC4J-TWP-JNDI-STATE-10131.pdf) - [Similar pages](#)

**[PDF] JNDI State Replication in Oracle Application Server 10g (10.1.2 ...)**

File Format: PDF/Adobe Acrobat - [View as HTML](#)

JNDI State Replication in Oracle Application Server 10g (10.1.2 and 10.1.3). Page 5.

Binding a Remote Object. If you bind a remote object (typically a home ...)

[www.oracle.com/technology/tech/java/oc4j/1013/whitepapers/oracleas1013\\_jndi\\_staterp\\_twp.pdf](http://www.oracle.com/technology/tech/java/oc4j/1013/whitepapers/oracleas1013_jndi_staterp_twp.pdf) - [Similar pages](#)

**J2EE BluePrints: -**

Entity beans live even after a client's session with the **server** is over and ... Some containers may not be capable of handling complex **state objects** (for ...

[java.sun.com/blueprints/guidelines/designing\\_enterprise\\_applications\\_2e/ejb-tier/ejb-tier6.html](http://java.sun.com/blueprints/guidelines/designing_enterprise_applications_2e/ejb-tier/ejb-tier6.html) - 12k - [Cached](#) - [Similar pages](#)

**Designing Enterprise Applications with the J2EE Platform, Second ...**

The **state** of a session **object** is non-persistent and need not be written ... Stateless session beans are designed strictly to provide **server-side** behavior. ...

[java.sun.com/blueprints/guidelines/designing\\_enterprise\\_applications\\_2e/ejb-tier/ejb-tier6.html](http://java.sun.com/blueprints/guidelines/designing_enterprise_applications_2e/ejb-tier/ejb-tier6.html) - 10k - [Cached](#) - [Similar pages](#)

**Adobe - Developer Center : Developing Flex RIAs with Cairngorm ...**

In **server**-side application development, one key challenge is that **state** often sits within ...

Introducing the Value Object / Data Transfer Object Pattern ...

[www.adobe.com/devnet/flex/articles/cairngorm\\_pt2\\_03.html](http://www.adobe.com/devnet/flex/articles/cairngorm_pt2_03.html) - 31k - [Cached](#) - [Similar pages](#)

**FlexBlog » Rich Internet Applications: State of the Union**

To put it simply, RIA isn't a set of pages controlled by the **server**; ... The application's **state** is controlled by a small Java applet running on the client. ...

[flexblog.faratasystems.com/?p=163](http://flexblog.faratasystems.com/?p=163) - 43k - [Cached](#) - [Similar pages](#)

**Administrative programs for multiple Java 2 Platform, Enterprise ...**

The **J2EE server** is not **state-manageable** because no start() operation is available on ... an array of **object names**, one for every module in the application. ...

[publib.boulder.ibm.com/.../v6r0/topic/com](http://publib.boulder.ibm.com/.../v6r0/topic/com).

[ibm.websphere.express.doc/info/exp/ae/cjmx\\_mult\\_appsrvr.html](http://ibm.websphere.express.doc/info/exp/ae/cjmx_mult_appsrvr.html) - 15k -  
[Cached](#) - [Similar pages](#)

**JSR-77 J2EE MIB Management**

The following are the notifications defined in the JSR-77 J2EE MIB:

j2eeServerStateChange: A **server** entered RUNNING, STOPPED, or FAILED state. ...  
www.adventnet.com/products/snmpadaptor/  
help/jboss\_snmp\_adaptor/jsr77\_j2ee\_mib\_management.html - 16k -  
Cached - Similar pages

### Spring Integration with WebLogic Server

WebLogic Server is a scalable, enterprise-ready J2EE application **server**. ... HTTP session state across servers within a cluster, WebLogic Server can also ...  
dev2dev.bea.com/pub/a/2005/09/spring\_integration\_weblogic\_server.html - 44k -  
Cached - Similar pages

Result Page:    [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#)    [\*\*Next\*\*](#)

---

(j2ee server) (state server) (state ob

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

---

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2007 Google